

Designation	Model NO.	Description
① Type	CZ-93	Safety switch
② Type of contact blocks fitted	B	2B(2NC)
	C	1A1B(1NC/1NO)
③ Conduit/connector size	PG	PG 13.5XP1.5(公制牙)
	PM	M20X1.5
④ Actuating keys	None	None
	01	Horizontal
	02	900 Vertical
	03	Adjustable

NOTE: The default size of conduit connector is M20x1.5.

Appearance and Dimension

Forced Disconnecting Mechanism

When the contact block get fire, press on the middle of the key structure, the NC strict leaving structure can push the contact block a way cut off the movement.

Ratings

Rated Voltage	Noninductive Load (A)				Inductive Load (A)			
	Resistance Load		Lamp Load		Inductive Load		Motor Load	
	NC	NO	NC	NO	NC	NO	NC	NO
125 VAC	10		3	1.5	10		5	2.5
250 VAC	10		2	1	10		3	1.5
400 VAC	10		1.5	0.8	3		1.5	0.8
8 VDC	10		6	3	10		6	6
14 VDC	10		6	3	10		6	6
30 VDC	6		4	3	6		4	4
125 VDC	0.8		0.2	0.2	0.8		0.2	0.2
250 VDC	0.4		0.1	0.1	0.4		0.1	0.1