

Starter package consisting of EASY-E4-AC-12RC1, patch cable and software license for easySoft $\,$



Part no. EASY-BOX-E4-AC1 197229

General specifications	
Product name	Eaton Moeller® series EASY Starter kit
Part no.	EASY-BOX-E4-AC1
EAN	4015080892908
Product Length/Depth	200 millimetre
Product height	135 millimetre
Product width	255 millimetre
Product weight	0.6 kilogram
Compliances	Eaton supports the product until its end of life
Certifications	IEC 60068-2-27 EN 55011 EN 55022 IEC 60068-2-6 IEC/EN 61000-4 IEC/EN 61000-4-2
Product Tradename	EASY
Product Type	Starter kit
Product Sub Type	None
Catalog Notes	depending on ambient air temperature fluctuations of up to ±5 s/day (±0.5 h/year) are possible
Features & Functions	
Fitted with:	Basic device Connection cable Control unit Software preinstalled Programming software
General information	
Insulation resistance	According to EN 50178
Mounting method	Screw fixing using fixing brackets ZB4-101-GF1 (accessories) Top-hat rail fixing (according to IEC/EN 60715, 35 mm)
Overvoltage category	III
Pollution degree	2
Туре	Starter kit
Ambient conditions, mechanical	
Drop and topple	50 mm Drop height, Drop to IEC/EN 60068-2-31
Mounting position	Vertical Horizontal
Shock resistance	15 g, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 11 ms, 18 Impacts
Climatic environmental conditions	
Air pressure	795 - 1080 hPa (operation)
Environmental conditions	Clearance in air and creepage distances according to EN 50178, UL 508, CSA C22.2 No. 142 Condensation: prevent with appropriate measures
Relative humidity	5 - 95 % (IEC 60068-2-30, IEC 60068-2-78)
Electro magnetic compatibility	
Air discharge	8 kV
Contact discharge	6 kV
Immunity to line-conducted interference	10 V (according to IEC/EN 61000-4-6)
Design verification	
10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.

10.2.2.2 Design of insul months abnormal heat/five by internal alast affects	Mastatha avadust standardla vasuiromanta
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects	Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation	Meets the product standard's requirements.
10.2.5 Lifting	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions	Meets the product standard's requirements.
10.3 Degree of protection of assemblies	Meets the product standard's requirements.
10.4 Clearances and creepage distances	Meets the product standard's requirements.
10.5 Protection against electric shock	Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components	Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections	Is the panel builder's responsibility.
10.8 Connections for external conductors	Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength	Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage	Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material	Is the panel builder's responsibility.
10.10 Temperature rise	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating	Is the panel builder's responsibility.
10.12 Electromagnetic compatibility	Is the panel builder's responsibility.
10.13 Mechanical function	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

Technical data ETHV 5.0	
Programmable logic controllers PLC (EG000024) / PLC device set (EC002581)	
Electric engineering, automation, process control engineering / Control, Process Control System (PCS) / Programmable logic control (SPS) / PLC device set (ecl@ss13-27-24-22-19 [BAA707018]	
Contains function building blocks	No
Contains basic device	Yes
Contains module rack	No
Contains power supply	No
Contains analogue input module	No
Contains analogue output module	No
Contains digital input module	No
Contains digital output module	No
Contains function module	No
Contains technology module	No
Contains communication module	No
Contains memory unit	No
Contains simulation module	No
Contains connection cable	Yes
Contains control unit	Yes
Contains monitor	No
Contains programming software	Yes
Contains engineering software	No
Contains visualization	No
Contains libraries	No
Contains documentation	No
Contains other components	No
Software preinstalled	Yes