



**Actuating rod, metal, +metal rod**

**Part no. LSM-XRRM  
266162**

<b>General specifications</b>	
Product name	Eaton Moeller® series LSM Accessory Actuating rod
Part no.	LSM-XRRM
EAN	4015082661625
Product Length/Depth	25 millimetre
Product height	200 millimetre
Product width	46 millimetre
Product weight	0.06 kilogram
Compliances	CE Marked
Certifications	UL 508 EN 60947-5 CSA Std. C22.2 No. 14 IEC 60947-5 UL IEC/EN 60947-5 UL Category Control No.: NKCR CSA Class No.: 3211-03 CSA File No.: 012528 UL File No.: E29184 CE CSA-C22.2 No. 14 CSA
Product Tradename	LSM
Product Type	Accessory
Product Sub Type	Actuating rod
<b>Features &amp; Functions</b>	
Features	The operating head can be rotated 90° to enable adaptation to the specified approach direction
Material	Metal base/bar Metal (Bar)
<b>General information</b>	
Product category	Actuating rod
Type	Operating heads
<b>Climatic environmental conditions</b>	
Ambient operating temperature - min	-25 °C
Ambient operating temperature - max	70 °C
<b>Actuator</b>	
Actuator type	Actuating rod
<b>Design verification</b>	
Equipment heat dissipation, current-dependent P <sub>vid</sub>	0 W
Heat dissipation capacity P <sub>diss</sub>	0 W
Heat dissipation per pole, current-dependent P <sub>vid</sub>	0 W
Rated operational current for specified heat dissipation (I <sub>n</sub> )	0 A
Static heat dissipation, non-current-dependent P <sub>vs</sub>	0 W
10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects	Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation	Please enquire
10.2.5 Lifting	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions	Meets the product standard's requirements.
10.3 Degree of protection of assemblies	Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances	Meets the product standard's requirements.

10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		Not applicable.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 9.0

Sensors (EG000026) / Cabezal de accionamiento de interruptor de posición/bisagra (EC001483)		
Tecnología electrónica, de automatización y de mando de procesos / Sensórica binaria, sens. orientada a la seguridad, tec. de medición de fabr. / Conmutador de posición / Cabezal de accionamiento de conmutador de posición (ecl@ss13-27-27-06-04 [BAA083017])		
Type of control element		Actuating rod