

## Button plate, flat red, STOP

Part no. M22-XD-R-GB0 218194



General specifications	
Product name	Eaton Moeller® series M22 Accessory Button plate
Part no.	M22-XD-R-GB0
EAN	4015082181949
Product Length/Depth	24 millimetre
Product height	3 millimetre
Product width	24 millimetre
Product weight	0.002 kilogram
Compliances	Contact Manufacturer
Certifications	UL File No.: E29184 CSA File No.: 012528 UL CSA Class No.: 3211-03 UL Category Control No.: NKCR CSA IEC/EN 60947 CSA-C22.2 No. 14 CE UL 508
Product Tradename	M22
Product Type	Accessory
Product Sub Type	Button plate
Features & Functions	
Color	Red
Design	Flush
Inscription	STOP Individual inscription possible: $\leq$ 5 characters: letter height 5 mm Individual inscription possible: $>$ 5 characters: letter height 3 mm
Inscription type	Text
Language	English
Shape	Round
General information	
Opening diameter	22.3 mm
Suitable for	Push button
Туре	Flat
Used with	M22-DZ-X M22(S)-DR-X M22-DG-X M22(S)-D-X
Climatic environmental conditions	
Ambient operating temperature - min	-25 °C
Ambient operating temperature - max	70 °C
Communication	
Connection to SmartWire-DT	No
Design verification	
Equipment heat dissipation, current-dependent Pvid	0 W
Heat dissipation capacity Pdiss	0 W
Heat dissipation per pole, current-dependent Pvid	0 W
Rated operational current for specified heat dissipation (In)	0 A
Static heat dissipation, non-current-dependent Pvs	0 W
10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects	Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation	Please enquire
10.2.5 Lifting	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions	Meets the product standard's requirements.
10.3 Degree of protection of assemblies	Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances	Meets the product standard's requirements.
10.5 Protection against electric shock	Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components	Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections	Is the panel builder's responsibility.
10.8 Connections for external conductors	Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength	Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage	Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material	Is the panel builder's responsibility.
10.10 Temperature rise	Not applicable.
10.11 Short-circuit rating	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## **Technical data ETIM 9.0**

Low-voltage industrial components (EG000017) / Legend plate for control circuit devices (EC000621) Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Button plate for command and alarm devices (ecl@ss13-27-37-12-24 [AKF042019]) Shape Round Construction type Flat Red Colour Stop Literal imprint English Language of the imprint Imprint ISO symbols None Imprint Other Engravable No Programme diameter mm 22 Width 24 mm Height 3 mm Outer diameter 22.5 mm Suitable for push button Yes Suitable for illuminated push buttons No Suitable for indicator light No Suitable for mushroom head push button No Suitable for signalling lamp No Suitable for selector switch No