DATASHEET - M22S-R30



Set of adapter rings

Part no.

EL Number (Norway) M22S-R30 216408 43555422



| General specifications | |
|--|--|
| Product name | Ecton Maellar® socias M22 Assessment Poduction ring out |
| | Eaton Moeller® series M22 Accessory Reduction ring set |
| Part no. EAN | M22S-R30 4015082164089 |
| | 10 millimetre |
| Product Length/Depth | |
| Product height | 50 millimetre |
| Product width | 50 millimetre |
| Product weight | 0.006 kilogram |
| Compliances | Contact Manufacturer |
| Certifications | UL/CSA certification not required |
| Product Tradename | M22 |
| Product Type | Accessory |
| Product Sub Type | Reduction ring set |
| Catalog Notes | Consists of adapter ring and lock nut |
| Features & Functions | |
| Bezel color | Black |
| Color | Black |
| General information | |
| Accessory/spare part type | Accessory |
| Degree of protection | IP66 IP69K IP67 |
| Climatic environmental conditions | |
| Ambient operating temperature - min | -25 °C |
| Ambient operating temperature - max | 70 °C |
| Communication | |
| Connection to SmartWire-DT | No |
| Contacts | |
| Force for positive opening - min | 0 N |
| Design verification | |
| • | |
| Equipment heat dissipation, current-dependent Pvid | 0 W |
| Heat dissipation capacity Pdiss | 0 W |
| Heat dissipation per pole, current-dependent Pvid | 0 W |
| Rated operational current for specified heat dissipation (In) | 0 A |
| Static heat dissipation, non-current-dependent Pvs | 0 W |
| 10.2.2 Corrosion resistance | Meets the product standard's requirements. |
| 10.2.3.1 Verification of thermal stability of enclosures | Meets the product standard's requirements. |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat | Meets the product standard's requirements. |
| 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects | Meets the product standard's requirements. |
| 10.2.4 Resistance to ultra-violet (UV) radiation | Please enquire |
| 10.2.5 Lifting | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.6 Mechanical impact | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.7 Inscriptions | Meets the product standard's requirements. |
| 10.3 Degree of protection of assemblies | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.4 Clearances and creepage distances | Meets the product standard's requirements. |
| 10.5 Protection against electric shock | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.6 Incorporation of switching devices and components | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.7 Internal electrical circuits and connections | Is the panel builder's responsibility. |

| 10.8 Connections for external conductors | Is the panel builder's responsibility. |
|--|--|
| 10.9.2 Power-frequency electric strength | Is the panel builder's responsibility. |
| 10.9.3 Impulse withstand voltage | Is the panel builder's responsibility. |
| 10.9.4 Testing of enclosures made of insulating material | Is the panel builder's responsibility. |
| 10.10 Temperature rise | Not applicable. |
| 10.11 Short-circuit rating | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.12 Electromagnetic compatibility | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.13 Mechanical function | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Accessories/spare parts for command devices (EC002024)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Command and alarm device (accessories) (ecl@ss13-27-37-12-92 [AC0037015])

| Type of electrical accessory/spare part | Other |
|---|---------------|
| Type of mechanical accessory/spare part | Reducing ring |
| Accessory | Yes |
| Spare part | No |