



CABLE LENGTH	TOLERANCE *								
ALL LENGTHS	+ 4% (OR 50mm) OF LENGT - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER								
STRIP LENGTH	TOLERANCE *								
0-7mm	±0.5mm ±1.0mm								
8-29mm									
30-49mm	±2.0mm ±3.0mm								
50-69mm									
70-100mm	±4.0mm								
OVER 100mm	±5.0mm								
* UNLESS OTHERWISE SPECIFIED									

NOTES:

- 1. "*" INDICATES CABLE LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTHS.
- 2. "/S1291" DESIGNATES PTFE TUBING AND SPECIAL CABLE.

	2. /S1291 DESIGNATES PIFE TUBING AND SPECIAL CABLE.							IV	02/09/16	RKE 4.4T-*-P7X2-RS 4.4T/S	1201	/C\/
3. "/SV" DESIGNATES SPECIAL PACKAGING FOR VENDING MACHINES.				SEE SPECIFICATIONS	DISPLAYED ON THIS	APVD	T.S.	SCALE 1=1.0	- INC 4.41-1-F/X2-N3 4.41/3128		/ 3 V	
	4. MAX LENGTH FOR VENDING MACHINE: 3.0 METERS.				FINISH	DRAWING ARE FOR REFERENCE ONLY	I UNII OF MEASUREMENT L			IDENTIFICATION NO.		REV
A	DRAWING RELEASE	TV	03/09/16		SEE SPECIFICATIONS	FOR MORE INFORMATION						А
RE	V DESCRIPTION	BY	DATE	ECO NO.			DO NOT SCA		E THIS DRAWING	FILE: 777037015	SHEET	1 OF 1
										•		

3RD ANGLE

PROJECTION

THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS

DOCUMENT WITHOUT
WRITTEN PERMISSION IS
PROHIBITED.

RELATED DOCUMENTS

2.

3.

MATERIAL

SOURCE DRAWING - FOR REFERENCE ONLY

turck lac

High Technology Sensors and Automation Controls

DATE 02/09/16 DESCRIPTION

3000 CAMPUS DRIVE

MINNEAPOLIS, MN 55441

1-800-544-7769

(763) 553-7300

turck.com

(763) 553-0708 fax