



**Overload relay, Ir= 1 - 1.6 A, 1 N/O, 1 N/C, Direct mounting**



**Part no.** ZE-1,6  
**014432**  
**EL Number** 4130479  
**(Norway)**

| General specifications                         |  |
|--|--|
| Product name                                   | Eaton Moeller® series ZE Thermal overload relay  |
| Part no.                                       | ZE-1,6   |
| EAN  | 4015080144328  |
| Product Length/Depth                           | 52 millimetre  |
| Product height                                 | 65 millimetre  |
| Product width                                  | 45 millimetre  |
| Product weight                                 | 0.075 kilogram   |
| Certifications                                 | IEC/EN 60947-5-1<br>IEC/EN 60947<br>CE<br>VDE 0660<br>CSA Class No.: 3211-03<br>CSA File No.: 012528<br>UL File No.: E29184<br>CSA<br>CSA-C22.2 No. 14<br>UL<br>IEC/EN 60947-4-1<br>UL 508<br>UL Category Control No.: NKCR  |
| Product Tradename                              | ZE   |
| Product Type                                   | Thermal overload relay   |
| Product Sub Type                               | None   |
| Catalog Notes                                  | Ambient air temperature: Operating range to IEC/EN 60947, PTB: -5°C to +50°C<br>Ambient operating temperature (according to IEC/EN 60947)<br>PTB: -5 °C - +55 °C<br>Rated operational current: Switch-on and switch-off conditions based on DC-13, time constant as specified. |
| Features & Functions                           |  |
| Features                                       | Phase-failure sensitivity (according to IEC/EN 60947, VDE 0660 Part 102)<br>Reset pushbutton manual/auto<br>Trip-free release<br>Test/off button   |
| General information                            |  |
| Ambient operating temperature - min            | -25 °C   |
| Ambient operating temperature - max            | 50 °C  |
| Ambient operating temperature (enclosed) - min | -25 °C   |
| Ambient operating temperature (enclosed) - max | 40 °C  |
| Class  | CLASS 10 A   |
| Climatic proofing                              | Damp heat, constant, to IEC 60068-2-78<br>Damp heat, cyclic, to IEC 60068-2-30   |
| Degree of protection                           | IP20   |
| Mounting method                                | Direct mounting<br>Direct attachment   |
| Overload release current setting - min         | 1 A  |
| Overload release current setting - max         | 1.6 A  |
| Overvoltage category                           | III  |
| Pollution degree                               | 3  |
| Product category                               | ZE overload relays for mini contactor relays   |
| Protection                                     | Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)   |
| Rated impulse withstand voltage (Uimp)         | 4000 V (auxiliary and control circuits)<br>6000 V AC   |
| Shock resistance                               | 10 g, Mechanical, Sinusoidal, Shock duration 10 ms   |
| Suitable for                                   | Branch circuits, (UL/CSA)  |
| Temperature compensation                       | ≤ 0.25 %/K, residual error for T > 40°   |

|   |  |  |
|---|--|--|
|   |  | Continuous   |
| <b>Terminal capacities</b>  |  |  |
| Terminal capacity (flexible with ferrule)   |  | 2 x (0.5 - 1.5) mm <sup>2</sup> , Main cables<br>1 x (0.5 - 1.5) mm <sup>2</sup> , Control circuit cables<br>1 x (0.5 - 1.5) mm <sup>2</sup> , Main cables   |
| Terminal capacity (solid)   |  | 1 x (0.75 - 2.5) mm <sup>2</sup> , Main cables<br>1 x (0.75 - 2.5) mm <sup>2</sup> , Control circuit cables<br>2 x (0.75 - 2.5) mm <sup>2</sup> , Control circuit cables                               |
| Terminal capacity (solid/stranded AWG)  |  | 18 - 14, Main cables<br>2 x (18 - 12), Control circuit cables  |
| Stripping length (main cable)   |  | 8 mm   |
| Stripping length (control circuit cable)  |  | 8 mm   |
| Screw size  |  | M3.5, Terminal screw   |
| Screwdriver size  |  | 2, Terminal screw, Pozidriv screwdriver<br>0.8 x 5.5 mm, Terminal screw, Standard screwdriver  |
| <b>Electrical rating</b>  |  |  |
| Conventional thermal current I <sub>th</sub> of auxiliary contacts (1-pole, open) |  | 6 A  |
| Rated operational current (I <sub>e</sub> ) at AC-15, 120 V                       |  | 1.5 A  |
| Rated operational current (I <sub>e</sub> ) at AC-15, 220 V, 230 V, 240 V         |  | 1.5 A  |
| Rated operational current (I <sub>e</sub> ) at AC-15, 380 V, 400 V, 415 V         |  | 0.7 A  |
| Rated operational current (I <sub>e</sub> ) at AC-15, 500 V                       |  | 0.5 A  |
| Rated operational current (I <sub>e</sub> ) at DC-13, 110 V                       |  | 0.4 A  |
| Rated operational current (I <sub>e</sub> ) at DC-13, 220 V, 230 V                |  | 0.2 A  |
| Rated operational current (I <sub>e</sub> ) at DC-13, 24 V                        |  | 0.9 A  |
| Rated operational current (I <sub>e</sub> ) at DC-13, 60 V                        |  | 0.75 A   |
| Rated operational voltage (U <sub>e</sub> ) - max                                 |  | 690 V  |
| Safe isolation  |  | 250 V AC, Between auxiliary contacts, According to EN 61140<br>300 V AC, Between auxiliary contacts and main contacts, According to EN 61140<br>300 V AC, Between main circuits, According to EN 61140 |
| Switching capacity (auxiliary contacts, general use)                              |  | 0.6 A, 600V AC, (UL/CSA)<br>1.5 A, 240V AC, (UL/CSA)   |
| Switching capacity (auxiliary contacts, pilot duty)                               |  | D300, AC operated (UL/CSA)<br>R300, DC operated (UL/CSA)   |
| <b>Short-circuit rating</b>   |  |  |
| Short-circuit current rating (basic rating)                                       |  | 5 kA, SCCR (UL/CSA)<br>6 A, max. Fuse, SCCR (UL/CSA)<br>15 A, max. CB, CB for max. 480 V, SCCR (UL/CSA)  |
| Short-circuit protection rating   |  | 6 A gG/gL, Fuse, Type "2" coordination<br>20 A gG/gL, Fuse, Type "1" coordination<br>Max. 4 A gG/gL, Fuse, Auxiliary contacts  |
| <b>Contacts</b>   |  |  |
| Number of auxiliary contacts (change-over contacts)                               |  | 0  |
| Number of auxiliary contacts (normally closed contacts)                           |  | 1  |
| Number of auxiliary contacts (normally open contacts)                             |  | 1  |
| Number of contacts (normally closed contacts)                                     |  | 1  |
| Number of contacts (normally open contacts)                                       |  | 1  |
| <b>Design verification</b>  |  |  |
| Equipment heat dissipation, current-dependent P <sub>vid</sub>                    |  | 5.1 W  |
| Heat dissipation capacity P <sub>diss</sub>                                       |  | 0 W  |
| Heat dissipation per pole, current-dependent P <sub>vid</sub>                     |  | 1.7 W  |
| Rated operational current for specified heat dissipation (I <sub>n</sub> )        |  | 1.6 A  |
| Static heat dissipation, non-current-dependent P <sub>vs</sub>                    |  | 0 W  |
| 10.2.2 Corrosion resistance   |  | Meets the product standard's requirements.   |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat        |  | Meets the product standard's requirements.   |
| 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects  |  | Meets the product standard's requirements.   |
| 10.2.4 Resistance to ultra-violet (UV) radiation                                  |  | Meets the product standard's requirements.   |
| 10.2.5 Lifting  |  | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.2.6 Mechanical impact  |  | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.2.7 Inscriptions   |  | Meets the product standard's requirements.   |
| 10.3 Degree of protection of assemblies   |  | Does not apply, since the entire switchgear needs to be evaluated.   |

|  |  |  |
|--|--|--|
| 10.4 Clearances and creepage distances                 |  | Meets the product standard's requirements.   |
| 10.5 Protection against electric shock                 |  | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.6 Incorporation of switching devices and components |  | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.7 Internal electrical circuits and connections      |  | Is the panel builder's responsibility.   |
| 10.8 Connections for external conductors               |  | Is the panel builder's responsibility.   |
| 10.9.2 Power-frequency electric strength               |  | Is the panel builder's responsibility.   |
| 10.9.3 Impulse withstand voltage                       |  | Is the panel builder's responsibility.   |
| 10.10 Temperature rise                                 |  | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating                             |  | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| 10.12 Electromagnetic compatibility                    |  | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| 10.13 Mechanical function                              |  | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.                         |

## Technical data ETIM 9.0

|  |   |                   |
|--|---|-------------------|
| Low-voltage industrial components (EG000017) / Thermal overload relay (EC000106)   |   |                   |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Overload protection device / Thermal overload relay (ecl@ss13-27-37-15-01 [AKF075019]) |   |                   |
| Adjustable current range   | A | 1 - 1.6           |
| Max. rated operation voltage U <sub>e</sub>  | V | 690               |
| Mounting method  |   | Direct attachment |
| Type of electrical connection of main circuit  |   | Screw connection  |
| Number of auxiliary contacts as normally closed contact  |   | 1                 |
| Number of auxiliary contacts as normally open contact  |   | 1                 |
| Number of auxiliary contacts as change-over contact  |   | 0                 |
| Release class  |   | CLASS 10 A        |
| Reset function input   |   | No                |
| Reset function automatic   |   | Yes               |
| Reset function push-button   |   | Yes               |