

Eaton 276691

Catalog Number: 276691

Eaton Moeller® series DILM Contactor, 3 pole, 380 V 400 V 4 kW, 1 N/O, 380 V 50 Hz, 440 V 60 Hz, AC operation, Screw terminals

General specifications



La foto es representativa

Product Name

Eaton Moeller® series DILM contactor

Catalog Number

276691

EAN

4015082766917

Product Length/Depth

75 mm

Product Height

68 mm

Product Width

45 mm

Product Weight

0.24 kg

Certifications

IEC/EN 60947

UL 60947-4-1

IEC/EN 60947-4-1

CSA-C22.2 No. 60947-4-1-14

UL File No.: E29096

CSA

CSA File No.: 012528

VDE 0660

CE

UL Category Control No.: NLDX

CSA Class No.: 2411-03, 3211-04

UL

Catalog Notes

Contacts according to EN 50012

Electrical connection type for auxiliary- and control-current circuit

Screw connection

Number Of Poles

Three-pole

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Characteristic curve

[eaton-contactors-switch-dilm-characteristic-curve-002.eps](#)

[eaton-contactors-switch-dilm-characteristic-curve.eps](#)

Declarations of conformity

[DA-DC-00004792.pdf](#)

[DA-DC-00004810.pdf](#)

Diagramas de cableado

[eaton-contactors-contact-dilm-wiring-diagram.eps](#)

Dibujos

[eaton-contactors-module-dilm-dimensions-002.eps](#)

[eaton-contactors-module-dilm-dimensions.eps](#)

[eaton-contactors-frame-dilm-dimensions.eps](#)

[eaton-contactors-dilm-3d-drawing-007.eps](#)

eCAD model

[DA-CE-ETN.DILM9-10\(380V50HZ,440V60HZ\)](#)

Instrucciones de instalación

[eaton-contactors-dila-dilm7-15-dilmp20-instruction-leaflet-il03407013z.pdf](#)

mCAD model

[DA-CS-dil_m7_15](#)

[DA-CD-dil_m7_15](#)

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

Operating frequency

9000 mechanical Operations/h (AC operated)

Pollution degree

3

Climatic proofing

Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78

Connection to SmartWire-DT

No

Rated impulse withstand voltage (Uimp)

8000 V AC

Utilization category

AC-3: Normal AC induction motors: starting, switch off during running

AC-4: Normal AC induction motors: starting, plugging, reversing, inching

AC-1: Non-inductive or slightly inductive loads, resistance furnaces

Connection

Screw terminals

Frame size

FS1

Ambient operating temperature - max

60 °C

Ambient operating temperature - min

-25 °C

Ambient operating temperature (enclosed) - max

40 °C

Ambient operating temperature (enclosed) - min

-25 °C

Ambient storage temperature - max

80 °C

Ambient storage temperature - min

-40 °C

Assigned motor power at 115/120 V, 60 Hz, 1-phase

0.5 HP

Assigned motor power at 200/208 V, 60 Hz, 3-phase

3 HP

Assigned motor power at 230/240 V, 60 Hz, 1-phase

1.5 HP

Assigned motor power at 230/240 V, 60 Hz, 3-phase

3 HP

Assigned motor power at 460/480 V, 60 Hz, 3-phase

5 HP

Assigned motor power at 575/600 V, 60 Hz, 3-phase

7.5 HP

Conventional thermal current i_{th} (1-pole, enclosed)

45 A

Conventional thermal current i_{th} (3-pole, enclosed)

18 A

Conventional thermal current i_{th} at 55°C (3-pole, open)

21 A

Conventional thermal current i_{th} of main contacts (1-pole, open)

50 A

Equipment heat dissipation, current-dependent P_{vid}

0 W

Heat dissipation capacity P_{diss}

0 W

Heat dissipation per pole, current-dependent P_{vid}

0.2 W

Application

Contactors for Motors

Product category

Contactors

Protection

Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)

Arcing time

10 ms

Electrical connection type of main circuit

Screw connection

Screwdriver size

0.8 x 5.5/1 x 6 mm, Terminal screw, Standard screwdriver
2, Terminal screw, Pozidriv screwdriver

Voltage type

AC

Degree of protection

IP20

Number of auxiliary contacts (normally closed contacts)

0

Number of auxiliary contacts (normally open contacts)

1

Number of contacts (normally closed) as main contact

0

Number of contacts (normally open contacts)

1

Number of main contacts (normally open contact)

3

Rated breaking capacity at 220/230 V

90 A

Rated breaking capacity at 380/400 V

90 A

Rated breaking capacity at 500 V

70 A

Rated breaking capacity at 660/690 V

50 A

Rated control supply voltage (Us) at AC, 50 Hz - max

380 V

Rated control supply voltage (Us) at AC, 50 Hz - min

380 V

Rated control supply voltage (Us) at AC, 60 Hz - max

440 V

Rated control supply voltage (Us) at AC, 60 Hz - min

440 V

Drop-out voltage

AC operated: 0.6 - 0.3 x UC, AC operated

Overvoltage category

III

Duty factor

100 %

Emitted interference

According to EN 60947-1

Interference immunity

According to EN 60947-1

Lifespan, mechanical

10,000,000 Operations (AC operated)

Pick-up voltage

0.8 - 1.1 V AC x Uc

Power consumption, pick-up, 50 Hz

24 VA, Dual-frequency coil in a cold state and 1.0 x Us, at 50 Hz

Safe isolation

400 V AC, Between coil and contacts, According to EN 61140

400 V AC, Between the contacts, According to EN 61140

Power consumption, pick-up, 60 Hz

30 VA, Dual-frequency coil in a cold state and 1.0 x Us, at 60 Hz

Screw size

M3.5, Terminal screw

Power consumption, sealing, 50 Hz

3.4 VA, Dual-frequency coil in a cold state and 1.0 x Us, at 50 Hz

1.4 W, Dual-frequency coil in a cold state and 1.0 x Us, at 50 Hz

Power consumption, sealing, 60 Hz

4.4 VA, Dual-frequency coil in a cold state and 1.0 x Us, at 60 Hz

1.4 W, Dual-frequency coil in a cold state and 1.0 x Us, at 60 Hz

Switching capacity (auxiliary contacts, general use)

1 A, 250 V DC, (UL/CSA)

10 A, 600 V AC, (UL/CSA)

Switching capacity (auxiliary contacts, pilot duty)

A600, AC operated (UL/CSA)

P300, DC operated (UL/CSA)

Terminal capacity (flexible with ferrule)

1 x (0.75 - 2.5) mm²

2 x (0.75 - 2,5) mm²

2 x (0.75 - 2.5) mm²

Shock resistance

7 g, N/O auxiliary contact, Mechanical, according to IEC/EN

60068-2-27, Half-sinusoidal shock 10 ms

5.7 g, N/O main contact, Mechanical, according to IEC/EN

60068-2-27 when tabletop-mounted, Half-sinusoidal shock 10 ms

3.4 g, N/C auxiliary contact, Mechanical, according to IEC/EN

60068-2-27 when tabletop-mounted, Half-sinusoidal shock 10 ms

5 g, N/C auxiliary contact, Mechanical, according to IEC/EN

60068-2-27, Half-sinusoidal shock 10 ms

10 g, N/O main contact, Mechanical, according to IEC/EN

60068-2-27, Half-sinusoidal shock 10 ms

3.4 g, N/O auxiliary contact, Mechanical, according to IEC/EN

60068-2-27 when tabletop-mounted, Half-sinusoidal shock 10 ms

Terminal capacity (solid)

2 x (0.75 - 2.5) mm²

1 x (0.75 - 4) mm²

Terminal capacity (solid/stranded AWG)

Single 18 - 10, double 18 - 14

Switching capacity (main contacts, general use)

20 A, Maximum motor rating (UL/CSA)

Tightening torque

1.2 Nm, Screw terminals

Rated control supply voltage (Us) at DC - max

0 V

Rated control supply voltage (Us) at DC - min

0 V

Rated insulation voltage (Ui)

690 V

Rated making capacity up to 690 V (cos phi to IEC/EN 60947)

112 A

Rated operational current (Ie) at AC-1, 380 V, 400 V, 415 V

22 A

Rated operational current (Ie) at AC-3, 220 V, 230 V, 240 V

9 A

Rated operational current (Ie) at AC-3, 380 V, 400 V, 415 V

9 A

Rated operational current (Ie) at AC-3, 440 V

9 A

Rated operational current (Ie) at AC-3, 500 V

7 A

Rated operational current (Ie) at AC-3, 660 V, 690 V

5 A

Rated operational current (Ie) at AC-4, 220 V, 230 V, 240 V

6 A

Rated operational current (Ie) at AC-4, 400 V

6 A

Rated operational current (Ie) at AC-4, 440 V

6 A

Rated operational current (Ie) at AC-4, 500 V

5 A

Rated operational current (Ie) at AC-4, 660 V, 690 V

4.5 A

Rated operational current (Ie) at DC-1, 110 V

20 A

Rated operational current (Ie) at DC-1, 220 V

15 A

Rated operational current (Ie) at DC-1, 60 V

20 A

Rated operational current for specified heat dissipation (In)

9 A

Rated operational power at AC-3, 240 V, 50 Hz

3 kW

Rated operational power at AC-3, 380/400 V, 50 Hz

4 kW

Rated operational power at AC-3, 415 V, 50 Hz

5.5 kW

Rated operational power at AC-4, 220/230 V, 50 Hz

1.5 kW

Rated operational power at AC-4, 240 V, 50 Hz

1.6 kW

Rated operational power at AC-4, 380/400 V, 50 Hz

2.5 kW

Rated operational power at AC-4, 415 V, 50 Hz

2.8 kW

Rated operational power at AC-4, 440 V, 50 Hz

3 kW

Rated operational power at AC-4, 500 V, 50 Hz

2.8 kW

Rated operational power at AC-4, 660/690 V, 50 Hz

3.6 kW

Rated operational power (NEMA)

3.7 kW

Rated operational voltage (Ue) at AC - max

690 V

Resistance per pole

2.5 m Ω

Static heat dissipation, non-current-dependent Pvs

1.4 W

Stripping length (control circuit cable)

10 mm

Stripping length (main cable)

10 mm

Switching time (AC operated, make contacts, closing delay) - max

21 ms

Switching time (AC operated, make contacts, closing delay) - min

15 ms

Switching time (AC operated, make contacts, opening delay) - max

18 ms

Switching time (AC operated, make contacts, opening delay) - min

9 ms

Short-circuit current rating (basic rating)

5 kA, SCCR (UL/CSA)

45 A, max. Fuse, SCCR (UL/CSA)

60 A, max. CB, SCCR (UL/CSA)

Short-circuit current rating (high fault at 480 V)

30/100 kA, Fuse, SCCR (UL/CSA)

65 kA, CB, SCCR (UL/CSA)

25 A, Class RK5/ 20 A Class J, max. Fuse, SCCR (UL/CSA)

16 A, max. CB, SCCR (UL/CSA)

Short-circuit current rating (high fault at 600 V)

30/100 kA, Fuse, SCCR (UL/CSA)

25 A, Class RK5/20 A, Class J, max. Fuse, SCCR (UL/CSA)

Short-circuit protection rating (type 1 coordination) at 400 V

35 A gG/gL

Suitable for

Also motors with efficiency class IE3

Short-circuit protection rating (type 1 coordination) at 690 V

20 A gG/gL

Short-circuit protection rating (type 2 coordination) at 400 V

20 A gG/gL

Short-circuit protection rating (type 2 coordination) at 690 V

16 A gG/gL

Special purpose rating of ballast electrical discharge lamps

18 A (480V 60Hz 3phase, 277V 60Hz 1phase)

18 A (600V 60Hz 3phase, 347V 60Hz 1phase)

Special purpose rating of definite purpose rating

54 A, LRA 480 V 60 Hz 3-ph, 100,000 cycles acc. to UL 1995, (UL/CSA)

9 A, FLA 480 V 60 Hz 3-ph, 100,000 cycles acc. to UL 1995, (UL/CSA)

Special purpose rating of elevator control

3 HP, 480 V 60 Hz 3-ph, (UL/CSA)

7.8 A, 200 V 60 Hz 3-ph, (UL/CSA)

2 HP, 240 V 60 Hz 3-ph, (UL/CSA)

6.8 A, 240 V 60 Hz 3-ph, (UL/CSA)

5 HP, 600 V 60 Hz 3-ph, (UL/CSA)

2 HP, 200 V 60 Hz 3-ph, (UL/CSA)

6.1 A, 600 V 60 Hz 3-ph, (UL/CSA)

4.8 A, 480 V 60 Hz 3-ph, (UL/CSA)

Special purpose rating of refrigeration control (CSA only)

- 10 A, FLA 480 V 60 Hz 3phase; (CSA)
- 60 A, LRA 600 V 60 Hz 3phase; (CSA)
- 60 A, LRA 480 V 60 Hz 3phase; (CSA)
- 10 A, FLA 600 V 60 Hz 3phase; (CSA)

Special purpose rating of resistance air heating

- 18 A, 600 V 60 Hz 3phase, 347 V 60 Hz 1phase, (UL/CSA)
- 18 A, 480 V 60 Hz 3phase, 277 V 60 Hz 1phase, (UL/CSA)

Special purpose rating of tungsten incandescent lamps

- 14 A, 480 V 60 Hz 3phase, 277 V 60 Hz 1phase, (UL/CSA)
- 14 A, 600 V 60 Hz 3phase, 347 V 60 Hz 1phase, (UL/CSA)

Conventional thermal current i_{th} at 40°C (3-pole, open)

22 A

Conventional thermal current i_{th} at 50°C (3-pole, open)

21 A

Conventional thermal current i_{th} at 60°C (3-pole, open)

20 A

Rated operational power at AC-3, 440 V, 50 Hz

5.5 kW

Rated operational power at AC-3, 500 V, 50 Hz

4.5 kW

Rated operational power at AC-3, 690 V, 50 Hz

4.5 kW

Actuating voltage

380 V 50 Hz, 440 V 60 Hz

Altitude

Max. 2000 m

Operating voltage at AC, 50 Hz - min

24 V

Operating voltage at AC, 50 Hz - max

690 V

Operating voltage at AC, 60 Hz - min

24 V

Operating voltage at AC, 60 Hz - max

690 V



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. Todos los
derechos reservados.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)