



Ba15d continuous light module; red

**Part no. SL7-L-R
171435**

| General specifications | |
|--|--|
| Product name | Eaton Moeller® series SL7 Continuous light module |
| Part no. | SL7-L-R |
| EAN | 4015081677672 |
| Product Length/Depth | 73 millimetre |
| Product height | 73 millimetre |
| Product width | 73 millimetre |
| Product weight | 0.075 kilogram |
| Certifications | IEC/EN 60947-5-1 UL UL File No.: E29184 CE UL Category Control No.: NKCR UL 508 CSA-C22.2 No. 14-10 CSA-C22.2 No. 94-91 IEC/EN 60529 CSA Class No.: NKCR7 Certified by UL for use in Canada UL report applies to both US and Canada |
| Product Tradename | SL7 |
| Product Type | Continuous light module |
| Product Sub Type | None |
| Catalog Notes | Without light elements |
| Features & Functions | |
| Color | Red |
| Enclosure color | Black |
| Functions | Continuous light |
| Light modules | Filament lamp max. 7 W |
| Number of modules | Max. 10 (with base for mounting on both sides) Max. 5 (with standard base) |
| General information | |
| Connection to SmartWire-DT | No |
| Degree of protection | IP66 NEMA 4X |
| Lifespan, electrical | 3,000 h |
| Light type | Continuous light |
| Material | Enclosure: Polycarbonate (PC) Cap: Polycarbonate (PC) |
| Mounting Method | BA15d lamp socket |
| Mounting position | As required |
| Overvoltage category | III |
| Pollution degree | 3 |
| Product Category | SL signal towers |
| Radiation angle | 360 ° |
| Rated impulse withstand voltage (Uimp) | 4000 V AC |
| Shock resistance | Mechanical, According to IEC/EN 60068-2-27 15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms |
| Type | Continuous light module |
| Voltage type | AC/DC |
| Climatic environmental conditions | |
| Ambient operating temperature - min | -30 °C |
| Ambient operating temperature - max | 60 °C |
| Climatic proofing | Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30 |

| Electrical rating | | |
|--|--|--------------------------------------|
| Leakage current | | 0.003 A |
| Power consumption | | Max. 7 W with the specified voltages |
| Rated insulation voltage (Ui) | | 250 V |
| Rated operational voltage (Ue) at AC - min | | 24 V |
| Rated operational voltage (Ue) at AC - max | | 250 V |
| Rated operational voltage (Ue) at DC - min | | 24 V |
| Rated operational voltage (Ue) at DC - max | | 250 V |

Technical data ETIM 9.0

| Low-voltage industrial components (EG000017) / Elemento de torre de señal, óptico (EC000232) | | |
|--|----|------------------|
| Tecnología electrónica, de automatización y de mando de procesos / Tecnología de conmutación de baja tensión / Equipo de comando y señalización / Columna óptica de señales (ecl@ss13-27-37-12-20 [AKF038019]) | | |
| Function | | Continuous light |
| Repetition frequency settable | | No |
| Colour | | Red |
| Outer diameter | mm | 73 |
| Operating voltage AC 50 Hz | V | 24 - 250 |
| Operating voltage AC 60 Hz | V | 24 - 250 |
| Operating voltage DC | V | 24 - 250 |
| Voltage type | | AC/DC |
| Power consumption | W | |
| Lamp type | | None |
| Housing colour | | Black |
| Degree of protection (IP) | | IP66 |
| Degree of protection (NEMA) | | 4X |